



شركة المطاط العالمية ذ.م.م.
INTERNATIONAL RUBBER COMPANY (L.L.C.)

DATA SHEET
TPE PROFILES GASKETS
FOR ALUMINIUM ARCHITECTURAL APPLICATION

Material : Vergin TPE

Function : Holding of Glass and Aluminium Sash. Excellent sealing against dust, water and winds, thermal Insulation, shock absorber, good aesthetic appearance.

General Physical Properties

Properties	Specifications	Test Method
Hardness (Shore A)	65° ± 5°	BS903
Specific Gravity	1.03	BS903
Elongation @ Break %	360 %	BS903
Tensile Strength (MPa)	5.1	BS903
Compression Set (%) 24 Hrs @ 25°C	25 %	BS903
Weather resistance	Good	BS903

International Rubber Co. has developed **TPE** suit all major Aluminium systems used in Middle East Region. With in-house Tool Room and R & D facilities, the response time to new Developments is very short.

Issue Date : 11-09-2003 | Doc. No. : QOD 001 | Rev. No. : 01 | Rev. Date : 11.09.02



ص.ب : ٢٧١٤٠، دبي، الامارات العربية المتحدة هاتف : +٩٧١ ٤ ٨٨٥٩٨٨٠، فاكس : +٩٧١ ٤ ٨٨٥٩٨٩٠
P.O. Box 27140, Dubai, U.A.E. Tel.: +971 4 8859880, Fax: +971 4 8859890
E-mail: ircruber@emirates.net.ae. Website: http://www.intrubber.com

